

British Parallel Flange Channels (PFC)

Available in spec and grades:
EN 10025-2:2004 S235JR, S275JR/J0/J2, S355JR/J0/J2

Dimensions and tolerances as per
BS 4-1:2005
EN 10279:2000

Designation	Dimensions					
	G (kg/m)	h (mm)	b (mm)	tw (mm)	tf (mm)	r (mm)
PFC 100 x 50 x 10	10.2	100	50	5.0	8.5	9
PFC 125 x 65 x 15	14.8	125	65	5.5	9.5	12
PFC 150 x 75 x 18	17.9	150	75	5.5	10.0	12
PFC 150 x 90 x 24	23.9	150	90	6.5	12.0	12
PFC 180 x 75 x 20	20.3	180	75	6.0	10.5	12
PFC 180 x 90 x 26	26.1	180	90	6.5	12.5	12
PFC 200 x 75 x 23	23.4	200	75	6.0	12.5	12
PFC 200 x 90 x 30	29.7	200	90	7.0	14.0	12
PFC 230 x 75 x 26	25.7	230	75	6.5	12.5	12
PFC 230 x 90 x 32	32.2	230	90	7.5	14.0	12
PFC 260 x 75 x 28	27.6	260	75	7.0	12.0	12
PFC 260 x 90 x 35	34.8	260	90	8.0	14.0	12
PFC 300 x 90 x 41	41.4	300	90	9.0	15.5	12
PFC 300 x 100 x 46	45.5	300	100	9.0	16.5	15
PFC 380 x 100 x 54	54.0	380	100	9.5	17.5	15
PFC 430 x 100 x 64	64.4	430	100	11.0	19.0	15

